



15 MAR 2008
 Byggingaútlagunni í Hátharfirði
 F.h. Hrólfur S. Gunnlaússon

GENERAL (if not mark on the drawing):
 ANCHORS M30-8.8 L= 730mm
 THICKNESS FOOT PLATE 25 mm,
 DOWN EDGE FOOT PLATE +50,

Stopy fundamentowe wykonać z betonu min C20/25 (B25)
 Concrete foundation -min C20/25 (B25)

3	C	Change 1 and 2	2008-11-18
2	B	Second issue, FOR CHECK	2008-11-18
1	A	First issue, FOR CHECK	2008-11-18
REV. NO.	REV. MARK	REVISION DESCRIPTION	REVISION DATE

GRADE: S235, UNLESS NOTED
 ALL WELDS ARE 1.0, 0.7min, F.W UNLESS NOTED
 ALL BOLTS ARE 8.8, UNLESS NOTED

PROJECT: Alcan
 DRAWING TITLE: Anchors view
 CONTRACTOR: **SPOMASZ**

SPOMASZ
 ZARY | POLAND

R.C.K.
 BIURO INŻYNIERSKIE SP. Z O.O.
 UL. SKORCKIEGO 39
 PL 61-538 POZNAŃ

CONTRACT NO. SPOMASZ: IT SP001882
 CONTRACT NO. R.C.K.: R-08-0114
 DRAWING NO.: G [1]
 REV. MARK: C

Rev.	Rev.	Rev.	Rev.	Rev.	Rev.	Rev.	Rev.	Rev.	Rev.
1	2	3	4	5	6	7	8	9	10

This drawing is the property of the Alcan Iceland Ltd. and handed out for personal use only. It may neither be copied nor made available to others without permission of the Alcan Iceland Ltd. The receiver is liable for any misuse.

Fjöldi stykja / Number of pieces	Hútur / Object	Alnir / Item	Efni / Material	ea. stk. / Weight	Ítalaf. heild / Total weight	Athugasemdir / Remarks
IV	Kersmiðja					
	Viðbygging við kersmiðju					
	Stávirki - Smíðateikning					
	VHE					
	RioTinto Alcan					

Páll P. Gunnarsson 2102597575