

OFNASKRÁR:

NR OFNS	REIKNAD VARMATAP WÖTT	MAX LENGÐ mm	MAX HÆÐ mm	STÚTAR	V A L D I R GERÐ OG HÆÐ cm	LENGD mm	O F N A R AFKÖST kcal/klis	wött
101	537	700	550	CD	PK+P59	640	532	677
102	938	2200	550	CD	P59	2160	330	1023
103	938	2200	550	CD	P59	2160	330	1023
104	938	2200	550	CD	P59	2160	330	1023
105	401	700	550	CD	PK50	720	349	406
106	401	700	550	CD	PK50	720	349	406
107	1513	2300	550	CD	PK59	2400	1349	1569
108	1513	2300	550	AD	PK59	2400	1344	1563
109	1513	2300	550	AD	PK59	2400	1344	1563
110	401	700	550	CD	PK50	720	349	406
111	401	700	550	CD	PK50	720	349	406
112	1134	2200	550	CD	PK50	2160	1047	1218
113	1134	2200	550	CD	PK50	2160	1047	1218
114	1134	2200	550	AB	PK50	2160	1047	1218
115	1134	2200	550	AB	PK50	2160	1047	1218
116	356	700	550	CD	P59	720	293	341
117	356	700	550	AB	P59	720	293	341
118	356	700	550	CD	P50	640	223	259
119	1134	2200	550	CD	PK50	2160	1047	1218
120	1134	2200	550	AB	PK50	2160	1047	1218
121	1139	1200	600	CD	PK+P59	1120	1018	1184
122	1139	1200	600	CD	PK+P59	1120	1018	1184
123	1139	1200	600	AB	PK+P59	1120	1018	1184
124	1139	1200	600	AB	PK+P59	1120	1018	1184
125	1139	1200	600	CD	PK+P59	1120	1018	1184
126	1139	1200	600	CD	PK+P59	1120	1018	1184
127	1139	1200	600	AB	PK+P59	1120	1018	1184
128	1139	1200	600	AB	PK+P59	1120	1018	1184
129	596	1200	600	CD	P59	1200	489	569
130	1629	2200	600	AB	P59/2	2080	1446	1632
131	1424	2300	450	BC	P44/2	2320	1254	1453
132	1424	2300	450	BC	P44/2	2320	1254	1453
133	1424	2300	450	BC	P44/2	2320	1254	1453
134	490	700	600	AB	PK59	720	403	469
135	979	1500	600	CD	PK59	1520	851	990
136	979	1500	600	AB	PK59	1520	851	990
137	490	700	600	CD	PK59	720	403	469
138	1424	2300	450	AD	P44/2	2320	1254	1453
139	1424	2300	450	AD	P44/2	2320	1254	1453
140	1424	2300	450	AD	P44/2	2320	1254	1453
141	1629	2200	600	AB	P59/2	2080	1446	1632
142	935	1500	600	CD	PK59	1440	807	939
143	312	700	600	AB	P59	640	261	304
144	312	700	600	CD	P59	640	261	304
145	935	1500	600	AB	PK59	1440	807	939
146	1228	2200	550	CD	PK50	2240	1036	1263
147	1228	2200	550	CD	PK50	2240	1036	1263
148	267	700	550	AB	P50	640	223	259
149	356	700	550	CD	P50	640	223	259
150	356	700	550	AB	P50	640	223	259
151	401	700	550	AB	PK50	720	349	406
152	401	700	550	AB	PK50	720	349	406
153	1237	2200	550	CD	PK50	2240	1036	1263
154	1237	2200	550	CD	PK50	2240	1036	1263
155	1237	2200	550	AB	PK50	2240	1036	1263
156	1237	2200	550	AB	PK50	2240	1036	1263
157	401	700	550	CD	PK50	720	349	406
158	401	700	550	CD	PK50	720	349	406
159	401	700	550	AB	PK50	720	349	406
160	401	700	550	CD	PK50	720	349	406
161	1566	2300	550	BC	PK59	2430	1339	1615
162	1566	2300	550	BC	PK59	2430	1339	1615
163	401	700	550	AB	P44	480	151	176
164	401	700	550	CD	PK50	720	349	406
165	401	700	550	AB	P44	480	151	176
166	401	700	550	AB	P44	480	151	176
167	1068	2200	550	CD	P59	2240	913	1062
168	1068	2200	550	CD	P59	2240	913	1062
169	1068	2200	550	CD	P59	2240	913	1062
170	537	700	550	AB	P59/2	720	501	583
Alls	64071			1.HÆÐ			Alls	64591

NR OFNS	REIKNAD VARMATAP WÖTT	MAX LENGÐ mm	MAX HÆÐ mm	STÚTAR	V A L D I R GERÐ OG HÆÐ cm	LENGD mm	O F N A R AFKÖST kcal/klis	wött
201	1157	2300	550	CD	P59	2320	946	1100
202	1157	2300	550	CD	P59	2320	946	1100
203	1157	2300	550	CD	P59	2320	946	1100
204	1113	2200	550	CD	P59	2240	913	1062
205	1575	3100	550	AD	P59	3120	1272	1479
206	1736	3400	550	AD	C7/2	3400	1493	1736
207	1736	3400	550	AD	C7/2	3400	1493	1736
208	1736	3400	550	AD	C7/2	3400	1493	1736
209	1575	3100	550	AD	P59	3120	1272	1479
210	1113	2200	550	CD	P59	2240	913	1062
211	1166	2300	550	CD	PK59	1840	1031	1199
212	1166	2300	550	AB	PK59	1840	1031	1199
213	1166	2300	550	AB	PK59	1840	1031	1199
214	587	700	550	CD	P59/2	720	501	583
215	587	700	550	AB	P59/2	720	501	583
216	312	700	550	AB	P59	640	261	304
217	312	700	550	CD	P59	640	261	304
218	223	700	550	CD	P50	480	168	195
219	490	1200	550	AB	P59	1040	424	493
220	490	1200	550	AB	P59	1040	424	493
221	490	1200	550	AB	P59	1040	424	493
222	490	1200	550	AB	P59	1040	424	493
223	490	1200	550	AB	P59	1040	424	493
224	490	1200	550	AB	P59	1040	424	493
225	490	1200	550	CD	P59	1040	424	493
226	490	1200	550	CD	P59	1040	424	493
227	490	1200	550	CD	P59	1040	424	493
228	490	1200	550	CD	P59	1040	424	493
229	490	1200	550	CD	P59	1040	424	493
230	490	1200	550	CD	P59	1040	424	493
231	409	1000	550	CD	P59	830	359	418
232	374	700	550	CD	P59	720	293	341
233	312	700	550	CD	P59	640	261	304
234	223	700	550	AB	P50	480	168	195
235	979	2400	550	BC	P59	2080	348	986
236	979	2400	550	BC	P59	2080	348	986
237	979	2400	550	BC	P59	2080	348	986
238	1380	1150	550	CD	PK59/2	1120	1114	1296
239	1380	1150	550	AD	PK59/2	1120	1114	1296
240	979	2400	550	AD	P59	1920	782	909
241	979	2400	550	AD	P59	1920	782	909
242	979	2400	550	AD	P59	1920	782	909
243	401	700	550	AB	P59	720	293	341
244	401	700	550	CD	P59	720	293	341
245	890	1300	550	AB	P59	1840	750	872
246	1130	2350	550	AB	P59	2320	946	1100
247	1130	2350	550	AB	P59	2320	946	1100
248	1130	2350	550	AB	P59	2320	946	1100
249	1059	2200	550	AB	P59	2240	913	1062
250	1495	3100	550	BC	P59	3120	1272	1479
251	1638	3400	550	BC	P59	3440	1402	1631
252	1638	3400	550	BC	P59	3440	1402	1631
253	979	2000	550	BC	P59	2000	815	948
254	490	800	550	CD	PK59	800	448	521
255	1166	3400	550	BC	PK59	3200	1792	2024
256	1273	3100	550	BC	P59	2720	1109	1290
257	979	2200	550	CD	P59	1920	782	909
258	979	2200	550	CD	P59	1920	782	909
259	1130	2350	550	CD	P59	2320	946	1100
260	1130	2350	550	CD	P59	2320	946	1100
261	1077	1200	550	AB	PK+P59	1040	945	1099
Alls	55509			2.HÆÐ			Alls	55260

NR OFNS	REIKNAD VARMATAP WÖTT	MAX LENGÐ mm	MAX HÆÐ mm	STÚTAR	V A L D I R GERÐ OG HÆÐ cm	LENGD mm	O F N A R AFKÖST kcal/klis	wött
301	312	800	550	AB	P59	640	261	304
302	401	700	550	AB	PK50	720	349	406
303	543	700	550	CD	P59/2	720	501	583
304	1744	1900	550	AB	PK+P59	1630	1527	1776
305	1744	1900	550	AB	PK+P59	1630	1527	1776
306	1299	1400	550	AB	PK+P50	1440	1140	1326
307	1299	1400	550	AB	PK+P50	1440	1140	1326
308	1299	1400	550	AB	PK+P50	1440	1140	1326
309	1299	1400	550	AB	PK+P50	1440	1140	1326
310	1317	2400	300	AB				1320
311	1299	1400	550	CD	PK+P50	1440	1140	1326
312	1299	1400	550	CD	PK+P50	1440	1140	1326
313	1299	1400	550	CD	PK+P50	1440	1140	1326
314	1299	1400	550	CD	PK+P50	1440	1140	1326
315	685	1200	550	CD	PK59	1040	583	678
316	1958	1200	550	AB	PK59/3	1200	1700	1977
317	543	800	550	AB	PK59	800	326	379
318	401	800	550	CD	P59	800	326	379
319	312	800	550	CD	P59	640	261	304
320	3435	5000	200	AD				3500