



SKÝRINGAR
 STEYPA=S350
 LOFTINNIHALD > 5%
 V/S-TALA < 0,45
 BENDISTÁL= Ks410
 FYLLING INN Í SÖKKLA SKAL VERA FRÖSTFRI OG ÞJAPPAST Í 30 SM LÖGUM
 UNDIRSTÖÐUR HVÍLA ÞJAPPADRI FYLLINGU
 ÞJÖPPUNARKRÖFUR E2 > 120 MPa, E2/E1 ≥ 2,3.
 MESTA ÁLAG Á UNDIRSTÖÐUR < 500 KN/M

BR.	DAGS.	EDLI BREITINGA	SIGN.
Strandgata 43 Hafnarfirði Undirstöður málteikn Samþykkt þann 04 NOV. 2004			
DAGS. nov 2004		Byggingafulltrúinn í Hafnarfirði F.h. Sigurbjartur Halldórsson	
VERK NR.			
TEIKN. NR. B-01.			
HANNAD SIG. ÞORLEIFSS. KT. 241148-3009			
TEIKNAD			
YFIRFARID <i>[Signature]</i>			
TÆKNIPJÓNUSTA SIGURDAR ÞORLEIFSSONAR ehf STRANDGÖTU 11 220 HAFNARFIRÐI Sími 555-4255 FAX 565-2875 E-mail taeknihjonusta@islandia.is			

Undirstöður Grunnmynd 1/50