



HANNAFRJÓÐUR
 BYGGINGARULLTRÖNN
 AFGREITT

Before removing Duct-tube a wire has to be fastened at one end of the tube in order to insert electrical cables etc. afterwards
 After temporary wire is inserted the hole has to be carefully cleaned with compressed air and the openings closed with a waterproof cover.



CONCRETE: C40/50-25-S2

REV. NO.	DATE	REVISION	BY	APP.	REV. NO.	DATE	REVISION	BY	APP.	NOTES	REFERENCE DRAWING	DRAWING NUMBER
3	1996.03.11	TOP OF ANODE COLUMNS	NI	N.I.								
2	1996.01.25	DUCT TUBES IN A1	FGS	N.I.								
1	1996.01.02	APPROVED FOR CONSTRUCTION	NI	N.I.								

VST VST CONSULTING ENGINEERS Ltd.
 Armúla 4 108 Reykjavík Iceland
 Tel: +354 569 5000 Fax: +354 569 5010

ICELANDIC ALUMINIUM COMPANY LTD.

DRAWN 05.10.28 FGS
 APPROVED 05.10.28 KGS
 PROCESS 05.10.28 NI
 PROJECT 05.10.28 NI
 SCALE 1:20

ALESA
 ALUSUISSE ENGINEERING LTD.
 ZÜRICH SWITZERLAND

ICELANDIC ALUMINIUM CO. LTD

POTROOM NO. 3
 CONCRETE WORK
 ANODE COLUMNS, A1, A2 and A3
 FORMWORK

79000-32330

186.630

07-NOV-1995 I:\95-1001\351201\DWG\DWG-C\AL-C130.DWG