

OFNALISTI KJALLARA

NR.	Nauðsynleg afköst [W]	Gerð/hæð [mm]	Lengd [mm]	Afköst við dT=40°C [W]	Stúta staðs. 10mm	Stíllitla ofnloka
001	531	VKL+V/(21)/400	800	531	CD	2
002	777	V2(H2)/(20)/500	1400	777	AB	3
003	1611	CP/(22)/500	1400	1611	CD	4
Samtals:		2919		2919		

OFNALISTI 1 HÆD

NR.	Nauðsynleg afköst [W]	Gerð/hæð [mm]	Lengd [mm]	Afköst við dT=40°C [W]	Stúta staðs. 10mm	Stíllitla ofnloka
101	1640	CP/(22)/210	2400	1640	AD	4
102	1640	CP/(22)/210	2400	1640	BC	4
103	1640	CP/(22)/210	2400	1640	BC	4
104	1640	CP/(22)/210	2400	1640	AD	4
105	1640	CP/(22)/210	2400	1640	AD	4
106	1640	CP/(22)/210	2400	1640	AD	4
107	1640	CP/(22)/210	2400	1640	AD	4
108	1640	CP/(22)/210	2400	1640	AD	4
109	1640	CP/(22)/210	2400	1640	AD	4
110	1640	CP/(22)/210	2400	1640	AD	4
111	1640	CP/(22)/210	2400	1640	AD	4
112	1640	CP/(22)/210	2400	1640	AD	4
113	1640	CP/(22)/210	2400	1640	AD	4
114	1640	CP/(22)/210	2400	1640	AD	4
115	1640	CP/(22)/210	2400	1640	BC	4
116	1640	CP/(22)/210	2400	1640	BC	4
117	1640	CP/(22)/210	2400	1640	BC	4
118	1093	CP/(22)/210	1600	1093	BC	4
119	1093	CP/(22)/210	1600	1093	AD	4
120	1640	CP/(22)/210	2400	1640	AD	4
121	1640	CP/(22)/210	2400	1640	AD	4
122	1640	CP/(22)/210	2400	1640	AD	4
123	1640	CP/(22)/210	2400	1640	BC	4
124	2160	(21)/500	2400	2160	BC	5
125	1230	CP/(22)/210	1800	1230	CD	4
126	1230	CP/(22)/210	1800	1230	CD	4
127	1620	(21)/500	1800	1620	CD	4
128	1230	CP/(22)/210	1800	1230	CD	4
129	1230	CP/(22)/210	1800	1230	CD	4
130	1230	CP/(22)/210	1800	1230	CD	4
131	1230	CP/(22)/210	1800	1230	CD	4
132	1230	CP/(22)/210	1800	1230	CD	4
133	1230	CP/(22)/210	1800	1230	CD	4
134	1230	CP/(22)/210	1800	1230	CD	4
135	1230	CP/(22)/210	1800	1230	CD	4
136	1230	CP/(22)/210	1800	1230	CD	4
137	1230	CP/(22)/210	1800	1230	CD	4
138	1230	CP/(22)/210	1800	1230	CD	4
139	1230	CP/(22)/210	1800	1230	CD	4
140	2160	(21)/500	2400	2160	AD	4
141	4200	VK+KV/(35)/210	3500	4200	AB	6
142	4200	VK+KV/(35)/210	3500	4200	AB	6
Samtals:		68186		68186		

OFNALISTI 4 HÆD

NR.	Nauðsynleg afköst [W]	Gerð/hæð [mm]	Lengd [mm]	Afköst við dT=40°C [W]	Stúta staðs. 10mm	Stíllitla ofnloka
401	1640	CP/(22)/210	2400	1640	AD	4
402	1640	CP/(22)/210	2400	1640	BC	4
403	1640	CP/(22)/210	2400	1640	BC	4
404	1640	CP/(22)/210	2400	1640	AD	4
405	1640	CP/(22)/210	2400	1640	AD	4
406	1640	CP/(22)/210	2400	1640	AD	4
407	1640	CP/(22)/210	2400	1640	AD	4
408	1640	CP/(22)/210	2400	1640	AD	4
409	1640	CP/(22)/210	2400	1640	AD	4
410	1640	CP/(22)/210	2400	1640	AD	4
411	1640	CP/(22)/210	2400	1640	AD	4
412	1640	CP/(22)/210	2400	1640	AD	4
413	1640	CP/(22)/210	2400	1640	AD	4
414	1640	CP/(22)/210	2400	1640	AD	4
415	1640	CP/(22)/210	2400	1640	BC	4
416	1640	CP/(22)/210	2400	1640	BC	4
417	1640	CP/(22)/210	2400	1640	BC	4
418	1093	CP/(22)/210	1600	1093	BC	4
419	1093	CP/(22)/210	1600	1093	AD	4
420	1640	CP/(22)/210	2400	1640	AD	4
421	1640	CP/(22)/210	2400	1640	AD	4
422	1640	CP/(22)/210	2400	1640	AD	4
423	1640	CP/(22)/210	2400	1640	BC	4
424	2160	(21)/500	2400	2160	BC	5
425	1260	(21)/500	1400	1260	CD	4
426	1260	(21)/500	1400	1260	CD	4
427	1260	(21)/500	1400	1260	CD	4
428	2505	CP/(22)/280	3000	2505	CD	5
429	1260	(21)/500	1400	1260	CD	4
430	1260	(21)/500	1400	1260	CD	4
431	1260	(21)/500	1400	1260	CD	4
432	1260	(21)/500	1400	1260	CD	4
433	1260	(21)/500	1400	1260	CD	4
434	1260	(21)/500	1400	1260	CD	4
435	1260	(21)/500	1400	1260	CD	4
436	1260	(21)/500	1400	1260	CD	4
437	1260	(21)/500	1400	1260	CD	4
438	1260	(21)/500	1400	1260	CD	4
439	1260	(21)/500	1400	1260	CD	4
440	2505	CP/(22)/280	3000	2505	CD	5
441	1260	(21)/500	1400	1260	CD	4
442	1260	(21)/500	1400	1260	CD	4
Samtals:		66116		66116		

Á ALLA OFNA KOMI FRAMRÁSALOKAR, STILLITÉ, AFTÆMING OG LOFTSKRÚFA STILLITAFLA MIDAST VID HEIMEIER OFNLOKA

OFNALISTI 2 HÆD

NR.	Nauðsynleg afköst [W]	Gerð/hæð [mm]	Lengd [mm]	Afköst við dT=40°C [W]	Stúta staðs. 10mm	Stíllitla ofnloka
201	1640	CP/(22)/210	2400	1640	AD	4
202	1640	CP/(22)/210	2400	1640	BC	4
203	1640	CP/(22)/210	2400	1640	BC	4
204	1640	CP/(22)/210	2400	1640	AD	4
205	1640	CP/(22)/210	2400	1640	AD	4
206	1640	CP/(22)/210	2400	1640	AD	4
207	1640	CP/(22)/210	2400	1640	AD	4
208	1640	CP/(22)/210	2400	1640	AD	4
209	1640	CP/(22)/210	2400	1640	AD	4
210	1640	CP/(22)/210	2400	1640	AD	4
211	1640	CP/(22)/210	2400	1640	AD	4
212	1640	CP/(22)/210	2400	1640	AD	4
213	1640	CP/(22)/210	2400	1640	AD	4
214	1640	CP/(22)/210	2400	1640	AD	4
215	1640	CP/(22)/210	2400	1640	BC	4
216	1640	CP/(22)/210	2400	1640	BC	4
217	1640	CP/(22)/210	2400	1640	BC	4
218	1093	CP/(22)/210	1600	1093	BC	4
219	1093	CP/(22)/210	1600	1093	AD	4
220	1640	CP/(22)/210	2400	1640	AD	4
221	1640	CP/(22)/210	2400	1640	AD	4
222	1640	CP/(22)/210	2400	1640	AD	4
223	1640	CP/(22)/210	2400	1640	BC	4
224	2211	(22)/700	1400	2211	EF	5
225	1260	(21)/500	1400	1260	CD	4
226	1260	(21)/500	1400	1260	CD	4
227	1260	(21)/500	1400	1260	CD	4
228	2505	CP/(22)/280	3000	2505	CD	5
229	1260	(21)/500	1400	1260	CD	4
230	1260	(21)/500	1400	1260	CD	4
231	1260	(21)/500	1400	1260	CD	4
232	1260	(21)/500	1400	1260	CD	4
233	1260	(21)/500	1400	1260	CD	4
234	1260	(21)/500	1400	1260	CD	4
235	1260	(21)/500	1400	1260	CD	4
236	1260	(21)/500	1400	1260	CD	4
237	1260	(21)/500	1400	1260	CD	4
238						
239	1260	(21)/500	1400	1260	CD	4
240	2505	CP/(22)/280	3000	2505	CD	5
241	1260	(21)/500	1400	1260	CD	4
242	1260	(21)/500	1400	1260	CD	4
243	1260	(21)/500	1400	1260	CD	4
244	2211	(22)/700	1400	2211	EF	5
Samtals:		66218		66218		

OFNI BREYTT OG HANN FÆRDUR

FJARLÆGDUR

OFNI BREYTT OG HANN FÆRDUR

OFNALISTI 5 HÆD

NR.	Nauðsynleg afköst [W]	Gerð/hæð [mm]	Lengd [mm]	Afköst við dT=40°C [W]	Stúta staðs. 10mm	Stíllitla ofnloka
505	649	CP/(22)/140	1000	649	CD	4
506	1557	CP/(22)/140	2400	1557	AD	4
507	649	CP/(22)/140	1000	649	AD	3
508	1557	CP/(22)/140	2400	1557	BC	4
509	649	CP/(22)/140	1000	649	AD	3
510	1557	CP/(22)/140	2400	1557	AD	4
511	1557	CP/(22)/140	2400	1557	AD	4
512	649	CP/(22)/140	1000	649	AD	3
513	1557	CP/(22)/140	2400	1557	AD	4
514	1557	CP/(22)/140	2400	1557	AD	4
515	649	CP/(22)/140	1000	649	AD	3
516	1557	CP/(22)/140	2400	1557	BC	4
517	649	CP/(22)/140	1000	649	BC	3
518	1298	CP/(22)/140	2000	1298	BC	4
523	1260	(21)/500	1400	1260	CD	4
524	649	CP/(22)/140	1000	649	AD	3
525	1260	(21)/500	1400	1260	CD	4
526	2505	CP/(22)/280	3000	2505	CD	5
527	1260	(21)/500	1400	1260	CD	4
528	1260	(21)/500	1400	1260	CD	4
529	1260	(21)/500	1400	1260	CD	4
530	1260	(21)/500	1400	1260	CD	4
531	1260	(21)/500	1400	1260	CD	4
532	1260	(21)/500	1400	1260	CD	4
533	1260	(21)/500	1400	1260	CD	4
534	1260	(21)/500	1400	1260	CD	4
535	1260	(21)/500	1400	1260	CD	4
536	1260	(21)/500	1400	1260	CD	4
537	1260	(21)/500	1400	1260	CD	4
538	2505	CP/(22)/280	3000	2505	CD	5
539	2187	(22)/500	1800	2187	CD	5
540						
541	1215	(22)/500	1000	1215	CD	4
542	649	CP/(22)/140	1000	649	BC	3
Samtals:		42181		42181		

OFNAR FJARLÆGDUR

OFNAR FJARLÆGDUR

OFNI BREYTT OFN FJARLÆGDUR OFNI BREYTT

Á ALLA OFNA KOMI FRAMRÁSALOKAR, STILLITÉ, AFTÆMING OG LOFTSKRÚFA STILLITAFLA MIDAST VID HEIMEIER OFNLOKA

OFNALISTI 3 HÆD

NR.	Nauðsynleg afköst [W]</
-----	-------------------------